



Installing your new HomeLink® visor.



Purchaser assumes all risk associated with the installation of all products we offer. VōZtech, its owners and employees, along with the manufacturer of each product, are not responsible for any direct or indirect damage to the vehicle or costs incurred from the installation or use of any products sold or otherwise provided.

970 Sunrise Ave, Ste 125-129, Roseville CA 95661

www.vetmods.com • www.voztech.com



Thank you for your purchase! Now its time to install and begin enjoying the added convenience of your new visor.

If you are removing an existing visor please read the instructions at the following link.

<http://www.vetmods.com/pdf/Visor%20instructions.pdf>

Step 1.

When installing the new visor you will want to first attach the wiring harness. This harness snaps together as shown in Fig. 1b. After making the connection you will want to tuck the connector up into the window header.



Fig. 1a



Fig. 1b

Step 2.

Insert the triangular bezel (Fig. 2a) into the ring at the window header (Fig. 2b). The bezel should only fit one way due to the unique shape of the triangular end.



Fig. 2a



Fig. 2b

Step 3.

970 Sunrise Ave, Ste 125-129, Roseville CA 95661

www.vetmods.com • www.voztech.com



Begin turning the visor towards the windshield while pressing up on the bezel ring (Fig. 3a, b & c). You will turn the visor beyond the point it snaps into the clip on the right. Just before reaching the windshield the bezel should snap fully into place as shown in Fig. 3d.



Fig. 3a



Fig. 3b



Fig. 3c



Fig. 3d

Step 4.

That's all there is to installing your new visor, now you just need to program the buttons to replace your existing remotes. Different units will require slightly different procedures so we refer you to the **HomeLink®** site for detailed instructions.

<http://www.homelink.com/training/train.taf>

Please contact us if you have any issues or require further assistance.

support@vettemods.com

Thanks, and enjoy your new <http://www.vettemods.com> product!